

## ABSTRACT

Provided is a display device having a storing circuit 21 section for storing image signals for controlling display and an active device section 22 for performing display control on the basis of the image signals stored by the storing circuit section 21, provided in each dot as a minimum unit of display, thereby achieving space saving.

(1)  
(2)  
(3)  
(4)  
(5)  
(6)  
(7)  
(8)  
(9)  
(10)  
(11)  
(12)  
(13)  
(14)  
(15)  
(16)  
(17)  
(18)  
(19)  
(20)  
(21)  
(22)  
(23)  
(24)  
(25)  
(26)  
(27)  
(28)  
(29)  
(30)  
(31)  
(32)  
(33)  
(34)  
(35)  
(36)  
(37)  
(38)  
(39)  
(40)  
(41)  
(42)  
(43)  
(44)  
(45)  
(46)  
(47)  
(48)  
(49)  
(50)  
(51)  
(52)  
(53)  
(54)  
(55)  
(56)  
(57)  
(58)  
(59)  
(60)  
(61)  
(62)  
(63)  
(64)  
(65)  
(66)  
(67)  
(68)  
(69)  
(70)  
(71)  
(72)  
(73)  
(74)  
(75)  
(76)  
(77)  
(78)  
(79)  
(80)  
(81)  
(82)  
(83)  
(84)  
(85)  
(86)  
(87)  
(88)  
(89)  
(90)  
(91)  
(92)  
(93)  
(94)  
(95)  
(96)  
(97)  
(98)  
(99)  
(100)